

The Sullair TSR-32 Air Compressor Designed for the Rental Industry.



Ideal for:

- Emergency air
- Standby air
- Supplemental air
- Peak load shaving

Rugged Package Design

- Self-contained package
- Cold weather protection
- Suited for use outdoors
- Oil field skid

- Fork lift pockets
- Heavy-duty sound-attenuated enclosure
- Easy-access doors
- Heavy-duty air inlet filter
- Air-cooled package

Total Versatility

These rental models are available with either variable speed drive or fixed speed. The variable speed drive and

Sullair spiral valve technology provides each compressor model with energy savings and a wide range capacities and pressures.

User-friendly, Rental-ready Features Include:

- Built-in circuit breaker
- Fully automated controls
- Cam lock connections



Energy Savings and Features are Built-In to the Sullair TSR-32 Electric Rental Package

Energy Savings

Energy savings are derived from:

- Variable speed drive
- Sullair's spiral valve
- Premium efficiency TEFC flanged mounted motor

Compressor Controllers

- The TSR-32 feature the Sullair Supervisor™ Microprocessor Controller

Total Flexibility to Meet a Variety of Specifications

- 13 models in one compressor
- 784 to 1600 acfm range
- 100 to 175 psig range
- Operating temperature range of 120°F to 20°F

Plus These Additional Sullair Features:

- Multi-stage air/fluid separation
- Low fluid carry-over—1 ppm maximum

- Spin-on fiberglass fluid filter
- Spill-proof base plate
- RS232 and RS485 ports for communications and remote monitoring
- Optional inline filters available to meet various air quality requirements
- HERESITE® coated coolers
- Fluid containment pan



All compressors are available with Sullair's Air Quality Guarantee.

Specifications for TSR-32

| Model | 200L | 200H | 200HH | 200XH | 250L | 250H | 250HH | 250XH |
|-------------------------------|-------------|-------------|--------------|--------------|------------------------------|------|-------|-------|
| Compressor Performance | | | | | | | | |
| Horsepower | 222 | 222 | 220 | 220 | 277 | 277 | 275 | 275 |
| Capacity ACFM | 1085 | 970 | 856 | 784 | 1346 | 1225 | 1108 | 1000 |
| Pressure PSIG | 100 | 125 | 150 | 175 | 100 | 125 | 150 | 175 |
| Model | 300L | 300H | 300HH | 300XH | TSR-32F (Fixed Speed) | | | |
| Compressor Performance | | | | | | | | |
| Horsepower | 333 | 333 | 330 | 330 | 325 | | | |
| Capacity ACFM | 1600 | 1435 | 1315 | 1225 | 1440 | | | |
| Pressure PSIG | 100 | 125 | 150 | 175 | 125 | | | |

Sullair offers air system solutions to help compressed air users reduce their energy costs and improve their productivity by analyzing, managing and controlling total compressed air systems. Information on the compressed air system tailored to your specific needs can be obtained by contacting your local Sullair Distributor. To acquire local distributor contact information visit us online at www.sullair.com or call 219-879-5451.



Sullair Corporation

3700 East Michigan Boulevard, Michigan City, IN 46360
Telephone: 1-219-879-5451

www.sullair.com

Sullair Corporation is a Hamilton Sundstrand Industrial business. Hamilton Sundstrand is a subsidiary of United Technologies Corp. (NYSE: UTX)
© Copyright 2010 Sullair Corporation. All rights reserved.
The color green is a registered trademark of Sullair Corporation.
Specifications subject to change without notice.

TS03E 1008R



The paper used in printing this literature was manufactured using recycled fiber, either pre-consumer or post-consumer waste, therefore less harmful to the environment because less virgin fiber is used, thereby reducing tree harvesting, water usage, energy consumption, emission of greenhouse gases and pollution.

